

BIDIRECTIONAL PRINTING METHOD AND  
APPARATUS WITH REDUCED COLOR UNEVENNESS

FIELD OF THE INVENTION AND RELATED ART:

5           The present invention relates to a bi-directional printing apparatus and a bi-directional printing method for effecting color print by scanning bi-directionally a printing material with a recording head for applying a plurality of (different) color  
10       inks at different ink amounts to the printing material, and more particularly to a bi-directional printing apparatus, a bi-directional printing method and a print wherein color non-uniformity attributable  
15       to bi-directional color print operation.

          In the field of a printing apparatus, particularly an ink jet type printing apparatus, increase of a recording speed for color print is desired. To meet this desire, increase of the length  
20       of the recording head, increase of the frequency of actuation of the recording head, bi-directional printing are generally considered. The bi-directional printing is advantageous in that required energy is less concentrated than a unidirectional printing and  
25       is scattered in terms of time under the same throughput, and therefore, it is advantageous in the cost as a total system.

          However, the bi-directional printing type is

0976454 0976454 0976454

disadvantageous in that it involves an essential problem that order of deposition or application or shot of the inks of different colors are different between the forward direction of the main-scanning and the backward direction thereof, depending on the structure of the recording head, and therefore, color non-uniformity in the form of bands results. The problem arises from the order of the ink applications, and therefore, a difference in the coloring more or less appears when different color dots are overlaid with each other even slightly.

When an image is formed by ejecting coloring materials such as pigment or dye ink onto a printing material, the ink first applied first dyes the printing material from the surface layer to the inside of the printing material. When a subsequent dot ink is applied in the manner that it at least partly overlaps with the prior ink dot, the subsequent ink dyes more at a portion below the already dyed portion, and therefore, there is a tendency that resultant color has a first-color-rich nature. On the other hand, in the case that ejection nozzles for different colors are arranged in the main scan direction, the order of ink shots in the forward scanning operation is opposite from the order of the ink shots in the backward scanning operation. Therefore, the band color non-uniformity occurs due to the difference in

the coloring.

The phenomenon occurs similarly in the case of wax type coloring material when a process color is formed due to the time difference, although the printing principles are different.

In the ink jet printer supporting the print, the problem is avoided using the following methods.

1) accept the color non-uniformity. Or, only black (Bk) is printed bi-directionally.

2) the nozzles for different colors are arranged in the sub-scan direction (so-called vertical arrangement).

3) the use is made with nozzles for forward path and nozzles for backward path, and the different nozzles or heads are used in the forward path and the backward path so that order of shots are the same.

Sub A-1  
4) the printing is effected such that rasters to be printed during the forward path and the backward path are interlaced, by which the frequency of the color non-uniformity due to the difference in the order of the shots is increased to provide visual uniformity (Japanese Patent Application Publication Hei 2-42421, Japanese Laid-open Patent Application Hei 7-112534).

When the method is used, dots of different diameters can be placed in the image, so that image of less granularity is perfected by relatively smaller

droplets, and a wide area is printed with relatively larger droplets with a smaller number of droplets, thus accomplishing a high speed and high quality printing.

5 For this, 2 kinds of methods have been widely proposed. More particularly, in a printing apparatus provided with a recording head capable of ejecting at least two sizes of liquid, that is, relatively larger droplets and relatively smaller droplets, A) the  
10 printing is carried out with single size droplets selected in accordance with a resolution or the like, B) different (at least two) droplet sizes of dots are mixed in accordance with the tone gradation data.

15 However, the conventional technique 1) does not provide a fundamental solution, and the throughput is significantly lower when a color image is printed. 2) the shot orders are the same in the forward path and the backward path, but the length of the recording head is large, and another difference in the coloring  
20 occurs due to the time difference in the shots of different colors.

25 3) this is equivalent to use independent two sets of recording heads even if the recording heads for the forward path and the backward path are built in the same substrate, and therefore, a color non-uniformity due to large color difference in the form of bands attributable to the difference of the

properties of different heads. For example, due to the difference in the data ratio of the forward path data to the backward path data, the temperature of the recording head may be different, there arises a difference in the ejection amounts between the recording heads, which would result in the color non-uniformity in the form of bands.

4) this provide regularly high frequency color non-uniformity to visually hide the color non-uniformity, but the color difference may be stressed by interference, depending on the print data. For example, when the color difference is produced for each raster line, a large color difference results

even if the same color is instructed, when there are a portion where the incidence is high on the even number rasters and a portion where the incidence is high on the odd number rasters in the forward path and the backward path due to half-tone process such as shading or the like.

In either of A) or B) for effecting color print using different droplet sizes, when the recording head for the respective colors are arranged in the main scan direction, and 1 path bi-directional printing is effected, the non-uniformity due to the bi-directional printing is conspicuous similarly to 3) and 4).

SUMMARY OF THE INVENTION:

Accordingly, it is a principal object of the present invention to provide a printing apparatus, a printing method and a print wherein the color non-uniformity attributable to the scanning directions can be reduced even if a bi-directional color print is carried out with different amounts of ink deposited.

It is another object of the present invention to provide a printing apparatus, a printing method and a print wherein the occurrence of the color non-uniformity attributable to the scanning direction irrespective of the print data with different amounts of ink deposited.

According to an aspect of the present invention, there is provided a printing apparatus for forming a color image by applying different color inks to a printing material while bi-directionally moving the recording head to scan the recording material, said apparatus comprising changing means for changing an order of applications of the inks of different colors to be applied at least at one amount for printing a secondary color to a secondary color pixel area; and forming means for forming the secondary color while making the order of applications of the inks to at least one of a plurality of the secondary color pixel areas arranged along a predetermined direction different from the order of another, by said

09764541 04504

changing means.

According to another aspect of the present invention, there is provided a printing apparatus for forming a color image by application of different color inks to a printing material while bi-directionally moving the recording head to scan the recording material, said apparatus comprising changing means for changing an order of applications of inks of different colors to be applied at least at one amount to form a process color in a process color pixel area; and forming means for forming the process color by making an order of applications of the inks to at least of the secondary color pixel areas arranged in a raster one direction different from the order of another, by said changing means.

According to a further aspect of the present invention, there is provided a printing apparatus for forming a color image by effecting scanning bi-directional movement of a recording head having recording elements corresponding to different color inks arranged symmetrically in a scanning direction and applying the color inks at different amounts, said apparatus comprising a plurality of print buffers corresponding to the recording elements arranged symmetrically; and distributing means for distributing print data for a color to be printed to at least one of the print buffers on the basis of an image signal

2025 RELEASE UNDER E.O. 14176

corresponding to the color image.

According to a further aspect of the present invention, there is provided a printing method for forming a color image by application of different color inks onto a printing material at different amounts while bi-directionally moving the recording head to scan the printing material, said method comprising: a first step of application of ink of a certain color ink at least at one amount to form a secondary color to a secondary color pixel area; and a second step of application of different color inks to form the secondary color in the secondary color pixel area in an order of applications which is different from the order in the first step.

According to a further aspect of the present invention, there is provided a print having a color image provided by different color inks, comprising: a printing material; a plurality of secondary color pixel areas arranged in a predetermined direction on the printing material; wherein the plurality of pixel areas are printed by different color inks at least at one amount, and wherein an order of applications of the inks to at least one of the pixel areas is different from the order of another.

With such a structure, the pixel areas of a process color including a secondary color, arranged in a predetermined direction such as the raster scan



direction, are dominantly provided by application of the inks in different application orders, and therefore, the orders of applications are substantially the same irrespective of the scanning directions so that generation of the color non-uniformity attributable to the order of applications of the inks can be reduced.

In this specification, "print" or "recording" includes formation, on a recording material, of significant or non-significant information such as an image, a pattern, character, figure and the like, and processing of a material on the basis of such information, visualized or non-visualized manner.

Here, the "recording or printing material" includes paper used in a normal printer, textile, plastic resin material, film material, metal plate and the like which can receive ink.

Here, "ink or liquid" includes liquid usable with the "print" or "recording" defined above, and liquid usable to formation of an image, pattern or the like on the printing material or to processing of the printing material.

The term "pixel area" means a minimum area where a primary color or secondary color is provided by application of one of more inks, and is not limited to a pixel but includes a super pixel or a sub-pixel. The number of scanings to complete the pixel area is

not limited to one but may be plural.

The term "process color" includes secondary colors, and means a color provided by mixing three or more colors on the printing material.

5           These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following description of the preferred embodiments of the present invention taken in conjunction with the  
10           accompanying drawings.

          These and other objects, features and advantages of the present invention will become more  
~~apparent upon a consideration of the following~~  
15           description of the preferred embodiments of the present invention taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS:

20           Figure 1 shows a substantial structure of an ink jet printing apparatus according to an embodiment of the present invention.

          Figure 2 is a block diagram of a control circuit for a printing apparatus.

25           Figure 3 shows an example of a recording head, an allotment of ejection nozzles and pixels according to an embodiment of the present invention.

          Figure 4 is a block diagram illustrating a

2025-10-10 14:39:26

5

0

5

20

25

Figure 12 illustrates production of color non-uniformity in bi-directional printing in prior art.

Figure 13 illustrates a structure of a pixel

in a multi-path printing according to Embodiment 4.

DESCRIPTION OF THE PREFERRED EMBODIMENTS:

5 in this embodiment, there is provided control means  
for effecting control such that when the use is made  
with a recording head having the recording nozzles for  
applying respective colors of inks at different  
amounts which are arranged symmetrically as seen at  
10 least in the main scan direction, for pixels which  
contains at least different color dots to be applied  
at least at one amount, the occurrence probabilities  
of different orders of printing of at least the  
different colors in the forward path print and the

15 backward path print are dominantly equal in effect.

In this case, the recording head may have nozzles  
having a relatively larger ejection amount and the  
nozzles having a relatively smaller ejection amount in  
combination, or the head may have a variably  
20 controllable ejection amount for each nozzle. By  
doing so, the color non-uniformity attributable to the  
bi-directional print, which have been caused by  
synchronism with the configuration data per se of a  
lateral ruler line or the like or by synchronism with  
25 half-toning in the dither or the like.

The above-described structure is effective in  
a half-tone area, particularly a low density portion  
of a color image, and for the high density portion, it

is effective that for one pixel, a plurality of dots of the same color ink is allotted with respect to at least one color of the used inks and that use is made with means for making it dominant that order of the shots of the inks constituting the second or higher color for a secondary or higher color is symmetrical.

The description will be made as to the embodiments of the present invention. In the Figures, the same reference numerals are assigned to the elements having the corresponding functions.

Figure 1 shows a structure of a major part of an ink jet printing apparatus according to an embodiment of the present invention.

As shown in Figure 1, a cartridge 1 is exchangeably mounted on a carriage 2. The head cartridge 1 comprises a print head portion, an ink container portion and a connector portion for receiving and supplying signals for driving the head portion (unshown).

The head cartridge 1 is carried on the carriage 2 at a correct position and is exchangeable, and the carriage 2 is provided with a connector portion and a holder (electrical connecting portion) for transmission of the driving signals or the like to the head cartridges 1 through the connector.

The carriage 2 is reciprocally supported and guided by a shaft 3 and a guide of the main assembly

of the apparatus, which is extended in a main scan direction. The carriage 2 is driven through a driving mechanism such as a motor, a pulley 5, a driven pulley 6, a timing belt 7 or the like by a main-scanning motor 4, and the position and the movement are controlled. A home position sensor 30 is carried on a carriage. By this, the position of the carriage 2 can be detected when the home position sensor 30 of the carriage 2 passes by the shielding plate 36.

The print mediums 8 in the form of a print sheet, thin plastic resin sheet or the like are fed out one by one from the automatic sheet feeder ("ASF") ~~by rotating the pick-up roller 31 through a gear by a~~ sheet feeding motor 35. By rotation of the feeding roller 9, the sheet is fed through (scanned by) a position (print portion) where the sheet is opposed to the ejection outlets of the head cartridge 1. The feeding roller 9 is rotated through the gear by rotation of the LF motor 34. At this time, the discrimination of the sheet feeding and the determination of the leading edge of the sheet is effected by the timing at which the print medium 8 passes by the paper end sensor 33. The paper end sensor 33 is also effective to detect the actual position of the trailing edge of the print medium 8 and to make the final determination of the current recording position.

The print medium 8 is supported by a platen (unshown) at its back side so as to provide a flat print surface at the print portion. The heads and cartridges 1 on the carriage 2 are supported such that ejection side surfaces thereof are faced downward in parallelism with the print medium 8 between the feeding rollers constituting a pair.

The head cartridge 1 is an ink jet head cartridge which ejects the ink using the thermal energy, and is provided with electrothermal transducers for generating thermal energy. In this example, the print head of the head cartridge 1 ejects the ink through the ejection outlet using the pressure of the bubble generated by film boiling caused by the thermal energy applied by the electrothermal transducer. Another type using a piezoelectric element to eject the ink, or the like is usable.

Figure 2 is a block diagram of a control circuit in the ink jet printing apparatus.

In these Figure, a controller 200 is a main controller, and comprises a CPU201 (a micro computer or the like), ROM203 storing a program, a table, fixed data or the like, and RAM205 having an area for conversion of image data and a wording area. The host apparatus 210 may be a supply source of image data (a computer for carrying out production and processing of data such as image to be printed, or a reader portion

00763454 012304  
105210 4948260

5

10

15

20

25



The head cartridge 1 is provided with a sub-heater 242. The sub-heater 242 functions for temperature adjustment for stabilizing the ink ejection property, and may be formed on the print head substrate simultaneously with the formation of the ejection heater 25 or may be mounted on the head cartridge or on the main body of the print head.

The motor driver 250 functions to actuate the main-scanning motor 4, and a sub-scan motor 34 functions to feed the print medium 8 (sub-scan), and the motor driver 270 is a driver therefor.

The sheet feeding motor 34 is a motor for separating and feeding the print medium 8 from the ASF, and the motor driver 260 is a driver therefor.  
(Embodiment 1)

Figure 3 is a partial schematic view of a major part of a recording head portion of a head cartridge 1. In this Figure, designated by 100 is a first recording head for ejecting cyan ink (C1). Designated by 101 is a first recording head (M1) for first recording heading magenta ink (M1).

Designated by 102 is a first recording head for ejecting yellow ink (Y1). Designated by 103 is a second recording head (Y2) for ejecting yellow ink. Designated by 104 is a second recording head (M2) for ejecting magenta ink. Designated by 105 is a second recording head (M2) for ejecting cyan ink.

Additionally, a recording head for ejecting Bk ink may be used, too.

The head cartridge 1 is constituted by such recording heads.

In head cartridge 1, each of the recording heads includes a plurality of ejection nozzles. For example, the recording head 100C1 includes cyan ejection nozzles 110 for ejecting a relatively larger size of droplet of cyan ink. The recording head 101M1 includes magenta ejection nozzles 112 for ejecting a relatively larger size of magenta droplet. The recording head 104M2 includes magenta ejection nozzles ~~113 for ejecting a relatively smaller size of magenta~~ droplet. The recording head 105C2 includes cyan ejection nozzles 111 for ejecting a relatively smaller size of cyan droplet.

The nozzles of each of the recording heads is arranged in a direction perpendicular to the main scan direction. Strictly, they may be slightly inclined relative to the main scan direction in consideration of the ejection timing. The recording heads are arranged in the same direction as the main scan direction. More particularly, in the case of Figure 2 example, each of the recording heads 100C1, 101M1, 102Y1, 103Y2, 104M2 and 105C2 is arranged in the same direction as the main scan direction.

The two recording heads for the respective

colors are disposed such that nozzles forejecting relatively larger droplets and the nozzles forejecting relatively smaller droplets are alternate in the opposite directions, that is, the nozzles forejecting the same amount of inks are disposed staggeredly.

Here, the intervals of the nozzles are arranged at the density of 720dpi, and therefore, the nozzles forejecting the relatively larger droplets are disposed at the density of 360dpi, and the relatively smaller droplet ejecting nozzles are disposed at the density of 360dpi.

In Figure 3, the dot positions 122, 123 of the pixel 130 is allotted with dots provided by relatively larger cyan and magenta droplets, and the positions 120, 121 are allotted with dots provided by relatively smaller droplets. The dot position 122 is the position to which the dot ejected through the ejection nozzle 110 of the recording head 100C1 and the dot ejected through the ejection nozzle 112 of the recording head 101M1 are allotted, for the area of the pixel 130.

The dot positions 122 in this Figure are the positions allotted for the dot provided by the ejection nozzle 117 of the recording head 104M2 and the dot provided by the ejection nozzle 115 of the recording head 105C2, both for area of the pixel (picture element) 130. In this example, the dot

position 122 is located on the upper right position of the diagonal line, and the dot position 123 is located on the upper left position.

5           The dot position respective in the same  
Figure is the position to which the dot ejected  
through the ejection nozzle 113 of the recording head  
104M2 and the dot ejected through the ejection nozzle  
111 of the recording head 105C2 are allotted for the  
10   region of the pixel 130. The dot position 121 in the  
same Figure, indicates the position to which the dot  
ejected through the ejection nozzle 114 of the  
recording head 100C1 and the dot ejected through t  
ejection nozzle 116 of the recording head 101M1 are  
15   allotted for the region of the pixel 130. Here, dot  
position 120 is the upper right diagonal position, and  
the dot position 121 is the lower left diagonal  
position. Designated by R1-R4 are main-scanning line  
for the pixels, namely, raster lines. Here, 1 pixel  
is provided by 2 raster scans.

20           Therefore, the pixels are arranged at the  
resolution of 360dpi x 360dpi.  
In the same Figure, the inks of the different colors  
are printed dot-on-dot in each pixel. The blue color  
(secondary color) is provided by cyan and magenta.  
25   The dot position 122 receives the ink from the magenta  
ejection nozzle 112 of the recording head 101M1 in the  
forward path, and then receives the ink from the cyan

09758454-01304  
T05270-45485260

ejection nozzle 110 of the recording head 100C1. From the above-described principle, the color of the first ink (magenta in this case) normally tends to be dominant, that is, the color is relatively closer to the burgundy color, at the dot position 121.

The same relation applies to portions 120, 121 to which the relatively smaller dots are allotted.

The print in the backward path will be considered. The ink from the cyan ejection nozzle 110 of the recording head 100C1 and the ink from the magenta ejection nozzle 112 of the recording head 101M1 are printed in this order. The color of the first ink (magenta in this case) normally tends to be

dominant, that is, the color is relatively closer to the violaceous color, at the dot position 123.

Similarly, in the backward path, the dot position 120 receives the ink from the magenta ejection nozzle 113 of the recording head 104M2, and then receives the ink from the cyan ejection nozzle 111 of the cyan of the recording head 105C2. The color of the first ink (magenta in this case) normally tends to be dominant,

that is, the color is relatively closer to the burgundy color, at the dot position 123. The similar relation applies to the position where the relatively small size droplet nozzles 120 and 121 are allotted.

The same relation applies to portions 120, 121 to which the relatively smaller dots are allotted.

00758454-013501

In Figure 3, white circles indicate dots where the magenta ink is printed and then the cyan is printed thereafter, hatched circles indicate dots where the inks are deposited in the opposite order.

5 The dots are disposed at four corners, but this is not limiting, and may be any if they are in the pixel area. Further alternatively, all them may be printed dot-on-dot. Even in the deviated arrangement, the dots in the pixel area are generally overlapped partly  
10 with each other.

In this manner, the blue relatively closer to burgundy (burgundy blue) and the blue relatively  
~~closer-to-violaceous-(violaceous-blue)-are-always~~  
15 appear as a pair. Microscopically, the differently colored dots appear diagonally. When this is seen on the pixel 130 macroscopically, the orders of shots (applications) of the ink are such that the larger size dots and relatively smaller size dots are  
20 symmetrical in the pixel structures. Therefore, in the single pixel, the intermediary blue color can be uniformly provided.

In this invention, it is dominant that colors constituting a secondary color for a pixel are  
25 symmetrically printed for the pixel. In this example, the blue color (cyan and magenta) is taken as the secondary color, but it will be readily understood that present invention is applicable to the red

2025-10-19 13:20

(magenta and yellow) and to the green (cyan and yellow).

In this embodiment, 7-level data (3 bits) (level 1 means minimum density (non-ejection); and level 7 means the maximum ) for each one component color corresponding to each color are normally used. The number of bits is not limited to 3 bit, but may be 4 bit or the like. Furthermore, even when the 3 bit data are used, only predetermined levels may be used. Particularly, the bit number is determined in view of the relation between the recording resolution and the dot diameter from the standpoint of the design philosophy of the degrees of the tone gradation for each pixel and the maximum density, and the present invention is usable with any of them.

The pixels indicated by reference numerals 130 - 139 in Figure 3 show states of dots allotted in accordance with tone gradation data ranging between level 1 to level 7.

The pixel 133 in Figure 3 corresponding to a datum of level 5, which are printed by only relatively larger dots of the same head structure. The pixel 136 in Figure 3 corresponds to a datum of level 3, which are printed by only relatively smaller dots of the same head structure. Each of these pixels constitutes a 2 dot pair for each size, and therefore, the result is that pixel structure is such that relatively larger

dot and the relatively smaller dot are disposed symmetrically irrespective of whether they are printed in the forward path or in the backward path.

5 Therefore, looking at each pixel, the blue coloring is uniform.

The pixel 139 corresponds to level 1 data, that is, no print. In this case, no ink is applied, so that there is no need of considering difference in the coloring attributable to the difference in the scanning moving direction.

10 When a half-tone image other than those described above within the pixel, the 2 dot pair ~~result in the maximum density in the same size, and~~ therefore, the dots are unable to be allotted in the 2 dot pair type. Namely, any pairing of dots with symmetrical shooting order cannot be used.

15 In this embodiment, for such dots of each pixel, the control is effected such that occurrence probabilities, in the forward path and the backward path, of at least the pixels in which the order of prints for each color are different, are substantially the same, by which the coloring provided by the forward path printing and the coloring provided by the backward path printing are macroscopically the same.

20  
25 Pixel 131 and pixel 132 show the dot arrangement corresponding to level 6 data. In pixel 131 and pixel 132, the relatively larger dots are

2025 RELEASE UNDER E.O. 14176



symmetrical in the printing order in the forward path and in the backward path, but at positions 120, 121, the dot disposition is such that relatively smaller dots where the order of printing is opposite only at one side. In the pixel 131, the number of blue dots which are relatively closer to the violaceous color (the coloring of cyan which has been shot first is dominant). Since the dots are relatively smaller dots, the influence is less significant than the relatively larger dots, but the hue is a little different. In the pixel 131, the number of blue dots which are relatively closer to the burgundy color (the coloring of magenta is dominant). Since the dots are relatively smaller dots, the influence is less significant than the relatively larger dots, but the hue is a little different.

Pixel pixel 137 and pixel pixel 138 show the dot arrangement corresponding to level 2 data. At the positions 137, 138, the use is made only with relatively small dots which are shot in opposite order only at one side. Therefore, the pixel at 137 is blue which is relatively closer to violaceous color (closer the cyan which has been shot first).

The pixel at 138 is, on the contrary, blue which is relatively closer to burgundy color (closer the cyan which has been shot first). The same applies to the pixels 134, 135 which correspond to the data of

level 4.

In this embodiment, a plurality of dot arrangements corresponding to the same level data (pixel 131 and 132 for the data of level 6, for example) are switched over both in the forward path and backward path of the print scanning, that is, the asymmetrical shooting order is switched in the recording scan. For the switching, the use is made with a recording head in which the shooting orders of the nozzles for each color are symmetrical with respect to the main scan direction, which is one of the feature of this embodiment. In other words, the order of shooting can be changed in the one main

recording scan by selecting which recording nozzle of the two same color symmetrical nozzles are arranged in the main scan direction, is allotted to the dot.

In this embodiment, when the dots are assigned for the data of each color, the dot-on-dot structure is provided, as shown in Figure 3. However, even if the dot is allotted to the position deviated in the main scan direction, another deviated position is satisfactory if it is within the pixel area.

Figure 7 shows a data buffer structure of the printing apparatus according to this embodiment.

In this figure, a printer driver 211 is actuated by a program for generating image data in a host apparatus 210 and for supplying the generated

data to the printing apparatus. The controller 200 converts the image data supply from the printer driver 211 if necessary and distributes them as 4 bit data for each color (CMY) per pixel. The distribution circuit 207 writes the data for each of CMY colors in the print buffer 205 such that the dots are allotted to meet the dot allotments and levels shown in Figure 3.

For example, 3 bit data at 360dpi are written for the cyan color (levels 1-7 in Figure 3. In the type of the embodiment, 2 bit data is written in the buffers 205C1, 205C2 for the recording heads 100C1 and 105C2, respectively (4-bits in total). When the recording heads reach the predetermined positions for the recording for the pixels, the data in the buffer are read in the registers in the recording heads to effect the printing operations. By such data and the buffer structure, the printing can be effected on the sub-pixels from the different recording heads, for the 2 dot pairs. Here, the CMY is taken, but the same applies to the case of CMYK, to the case of light and dark inks or other colors.

At this time, several combination of dots is possible depending on the way of writing the respective data. When all of the sizes of dots are used as with the pixel 130 shown in Figure 3, that is, when the level is at 7, "11" is written in the C1

buffer 205C1 shown in Figure 4. The value "11" is indicative of ejecting the ink from both of the nozzle 110 for ejecting relatively larger ink droplets and the nozzle 114 for ejecting relatively smaller ink droplets. Similarly, "11" is written in the buffers 205M1, 205M2 of 205C2.

When the use is made with two dots having the relatively larger size and one dot having the relatively smaller size dance with the pixel 131 in Figure 3, that is, when the lateral is at 6, "10" is written in the C1 buffer 205C1 shown in Figure 4. The value "10" is indicative of ejecting the ink only from ~~the nozzle 110 for ejecting relatively larger ink~~

droplets. Of the other hand, "11" is written in the C2 buffer 205C2. Similarly, the same is written in the buffer 205M1, 205M2.

In the case of level 6, as described hereinbefore, the distribution circuit 207 controls the writing into the buffer such that incidence probability of the pixel 131 and the incidence probability of the pixel 132 are substantially equal. When the pixel 132 is used, "11" is written in the C1 buffer 205C1 of Figure 4. On the other hand, "01" is written in the C2 buffer 205C2. The value "01" is indicative of ejecting the ink only from the nozzle 115 for ejecting relatively larger ink droplets. Similarly, the same is written in the buffer 205M1,

205M2.

In such a manner, the data is written in the buffers by the distributing circuit 207 such that in the incidence probabilities of the data "10" and "11" and the data "11" and "01" are substantially equal.

For the other levels 4, 2, the processing is the same as with lateral 6.

The print buffers 205C1, C2, M1, M2, Y1, Y2 are provided in a RAM205.

In such a case, the distribution may be alternating (sequential) distribution of the data to the plurality of (two, here) to the buffers or may be random distribution. What is desired is that orders of ink applications are not one-sided. More desirably, the incidences are fifty-fifty for the above-described reasons.

It is not necessarily to use all of the tone gradation levels shown in Figure 3. For example, in the high density portion, the density change saturate with respect to the number of dots allotted, and therefore, a binarization process may be carried out so that data containing only level 6.

When it is desired that spatial frequency is raised by reducing the intervals between the dots in an image so as to reduce the roughness of the image, that complete overlap of the dots is avoided or that non-uniformity in the form of stripes, the

With Figure 3, the description has been made with respect to the dot allotment for the cyan and magenta colors and blue color which is a secondary color provided by them, the same applies to the yellow and the other secondary color (green and red).

~~However, the present invention is not limited to these~~  
examples.

The symmetrical shape recording head usable with the present invention is not limited to the structure shown in Figure 3. For example, the recording heads shown in Figures 5 to 9 are considered as usable examples, but another structure is also usable if the advantageous effects of the present invention are provided.

Figure 5 shows an example having a structure similar to that of Figure 3 but additionally having a black recording head for ejecting black (K) ink at the left end, wherein only one yellow (Y) head is provided at the center of symmetry to simple the structure. The recording head provided at the center of symmetry, ejects the ink later at all times, that is, irrespective of the scanning directions. In this example, the yellow is disposed at the center, but this is not limiting.

Figure 5 shows an example which is similar to the example of Figure 3, but a black recording head for-ejecting-black\_(K)\_ink\_is added to the left-hand end, and only one yellow (Y) head located at the center of symmetry, by which the structure is simplified. The recording head at the center of the same entry prints later irrespective of the scanning direction. In this example, the yellow recording head is located at the center of the symmetry, but this is not limiting.

For the black recording head and the yellow recording head, only the nozzles for ejecting relatively larger droplets. The former is in order to provide high density for the black, and the latter is because that yellow color is less conspicuous.

Figure 6 shows an example which is similar to Figure 5 example, but the black recording head for

ejecting the black ink is omitted.

Figure 7 shows an example having a recording head for the black color in addition to the structure shown in Figure 12. The black is generally not used for printing the secondary color, and therefore, there is no need of symmetrical arrangement. In order to permit a higher speed printing operation in a monochromatic recording mode, the number of the nozzles for the black color is larger than that of the other chromatic head.

Figure 8 shows an example which is similar to Figure 6, but a black (K) recording head is added at a position of center of symmetry.

Figure 9 shows an example which is similar to Figure 7 example, but black recording date is located at the center of the symmetry.

(Embodiment 2)

The combinations of dots are not limited to those described in the foregoing, but various combinations are usable. In Figure 3, when the secondary color is to be printed, the dot-on-dot structure necessarily results, but this is not limiting, and the dot arrangement with which the dots do not tend to overlap with each other when the binarization process is effected.

Figure 10 shows an embodiment in which the dots are allotted in such a manner. The dot



arrangement of Figure 10 is similar to that of Figure 3, but an arrangement in which the dots are separated or deviated (pixels 140-147) is added to the dot arrangement (pixels 130-139).

5           For example, at level 6, pixels 140, 141 at which the relatively smaller dots are split (not dot-on-dot) are added. By the distribution circuit, the data are stored in the buffer such that incidence probabilities of the pixels 131, 132, 140, 141 at  
10           which the level is at 6, are substantially equal along the raster scan direction.

          At level 5, a pixel 142 at which relatively  
~~large dots are split (not dot-on-dot) is added.~~ In  
15           Embodiment 1, only one type of pixel structure for expressing level 5. In this embodiment, however, there are provided two kinds of pixel structures (pixels 133 and 142). The distribution circuit causes the buffer to store the data such that incidence probabilities of such pixels are substantially equal.

20           In this embodiment, the two dots are located diagonally in each of the pixel areas, that is, they are arranged separately. In Figure 10, however, the relatively larger dots are partly overlapped with each other, not completely overlapped though. But, the  
25           relatively smaller dot are hardly contacted to each other.

Figure 11 shows a specific example of dot

arrangement for the data of blue at level 2 and cyan at level 4, that is, cyan and magenta are at level 2 and at level 4, among the combination shown in Figure 10.

5 In this figure, the distribution circuit distributes the data such that incidence probabilities of the same level pixels are substantially equal in the raster scan direction and in the column direction (the direction in which the nozzles are arranged) as well. For example, the pixels of level 2 at the top in the Figure are arranged in the order of pixels 137, 138, 146, 147, in the direction of the raster scan,

10 ~~and the pixels of level 4 are arranged in the order of~~  
pixels 134, 135, 143, 144. On the other hand, the  
15 pixels of level 2 at the leftmost column are arranged in the order of pixels 137, 138, 146, 147 in the direction of column. The same as with the case of forward path applies to backward path.

20 As described in the foregoing, the control is effected such that occurrence probabilities of the pixels in which the order of prints for each color are different, are substantially equal in the forward and backward raster scan direction and in the direction of  
25 column, by which the coloring is substantially uniform macroscopically in the forward and backward directions and the direction of column.

In the pixels 142-147 added as the dot

arrangement responding to levels 5-2, the dots are separated, namely, the dot-on-dot does not exist, the spatial frequency is high so that densities of the dots are not high even when the macroscopic densities are the same, and therefore, the granularity of the image can be reduced. The effects are remarkable when the percentage of the added separation type pixels is increased by the distribution.

Moreover, the control may be effected such that data for the level (tone gradation) 2 and/or 4 do not result in dot-on-dot arrangement.

It is desirable that at least for the large dots with which the degree of overlapping between different colors is large, the incidence probabilities of the orders of shots (first and second) are substantially equal.

In this embodiment, when the relatively smaller dots are disposed diagonally in the pixel area, the dots are not contacted to each other, and therefore, the coloring is hardly influenced by the order of shots. Therefore, the pixels 146 and 147 having the added that arrangement is fixed to one of them, so that coloring is substantially uniform without the distribution. On the contrary, when the two 2 dot pair of the relatively larger dots such as the dots at level 6 is added with relatively smaller dot, the influence of the 2 dot pair in which the

order of shots is symmetrical are dominant, and therefore, the shots may be fixed one of the pixels 131, 132, 140, 141 without the distribution, by which the coloring is substantially uniform.

5

(Embodiment 3)

In Embodiment 1 described herein before, one pixel is constituted by a pair of two dots of the same size, and the order of shots of a pair of different size dots of the same color ink is symmetrical, at least for one color. In such examples, one pixel is constituted by a pair of two dots, and therefore, the examples are preferable when the maximum density of print is desirable such as when the images are formed on an OHP sheet. When the maximum density is not required, the maximum density may be provided by the relatively larger dot.

10

15

20

25

In Embodiment 2, for high density portions, the order of shots of the same coloring is symmetrical at least for one color as in the foregoing Embodiments, and in the half-tone portions, they use is made with a symmetrical recording head for bi-directional printing, and the combinations of the used recording heads are switched between when the recording heads scan in the forward direction and when it scans in the backward direction. By doing so, the half-tone can be expressed in addition to the high density portion, in the bi-directional print.

Patented 1993

It is known that so-called lateral a  
recording head unit in which the recording heads for  
the respective colors are arranged in the main scan  
direction is used for the bi-directional printing, the  
5 order of printing shots are different between when the  
recording heads scan in the forward direction and when  
it scans in the backward direction, and therefore, the  
coloring is different between them. As described in  
the foregoing, Japanese Patent Application Publication  
10 Hei 3-77066 proposes that combinations of the  
recording heads for the forward path and the recording  
heads for the backward path are arranged in the main  
~~scan-direction-so-as-to-accomplish-completely-the-same~~  
15 order of shots by properly switching the combinations.  
In this embodiment, the prior art is considered, and  
the advantageous effects is used.

In this embodiment, they use is made with  
switching the combinations of control between the high  
density portion and the low density portion in the  
20 manner described above. As compared with the  
completely different combinations, the maximum  
printing frequency of the recording elements can be  
reduced to one half. In other words, the recordable  
speed can be doubled.

25 When the image data are store at full address  
on the memory, and fully solid printing is carried  
out, the recording is effected by the forward

TOP SECRET

combination in the forward path and by the backward combination in the backward path in the conventional art, and therefore, it is required to provide the printing frequency meeting the allotment of dots to the full address with the recording element. With the conventional system, the maximum density can be allotted to the full address, and therefore, the maximum density is lowered, or otherwise, the printing speed has to be lowered.

According to the system of this embodiment, the printing is effected by the forward and backward combinations of a polarity of the dot diameters only for the low density portion, and for the high density portion, the recording is effected using both of them, and therefore, 1/2 recording frequency is enough to maximum for the full address. In the low density portion, the bi-directional non-uniformity may result due to variation of the recording elements or the like, the image non-uniformity adjacent to maximum density is significantly improved, and the printing speed is significantly enhanced.

(Embodiment 4)

The concept of the present invention is further developed, the color non-uniformity due to the bi-directional can be reduced, even when the symmetrical recording head for the bi-directional print. More particularly, in place of the 1 path bi-

directional print, a so-called multi-path print in which print of 1 pixel area is completed by a plurality of scans is used to accomplish the similar effects to the foregoing embodiments.

The description will be made as to an example in which a recording head having a laterally arranged C, M, Y recording elements is used, and blue dots are printed through bi-directional multi-path print.

Figure 12 shows a conventional example, and Figure 13 shows Embodiment 3 of the present invention. In the conventional example, the bidirectional print is simply carried out using large and small nozzles. In

this embodiment, the recording head scans the recording material in the forward direction, and thereafter, the recording head is moved relative to the recording material in the sub-scan direction at one half of one recording element pitch (here 2)  $\pm 1$  recording element pitch and three recording element pitch, and then, the recording head scans the recording material, thus effecting the multi-path print.

In the conventional example of Figure 12, the order of shots of the print data are influenced by the scanning direction with the result of color non-uniformity.

In this embodiment shown in Figure 13, a pixel is constituted by a pair of the dot for print in the forward path (122 and 121) and the dot for print in

the backward path (120 and 123), by which the order of shots is symmetrical for each dot size constituting the pixel, or by the dots are distributed such that asymmetrical dot arrangements appear substantially  
5 equally in the scanning direction when the arrangements are not symmetric, the uniform coloring is accomplished in the bi-directional.

At level 6 and 3, the relatively smaller dots provided by cyan first and those provided by magenta  
10 first, are uniformly distributed in the direction of the raster scan. At level 4, the relatively smaller dots provided by cyan first and those provided by magenta first, are uniformly distributed in the  
15 direction of the raster scan.

As described in the foregoing, the control is effected such that occurrence probabilities of the pixels in which the order of prints for each color are different, are substantially equal in the forward and  
20 backward raster scan direction, by which the coloring is substantially uniform macroscopically in the forward and backward directions. Therefore, the occurrences of color non-uniformity attributable to the order of application of ink in the bi-  
25 directional can be reduced.

In the foregoing embodiment, the control is effected such that occurrence probabilities of the pixels in which the order of prints for each color are

00765454 01504



different, are substantially equal in the forward and backward raster scan direction and in the direction of column, by which the coloring is substantially uniform macroscopically in the forward and backward directions and the direction of column. However, the present invention is not limited to this. The occurrence probabilities may be controlled in the predetermined direction in which the color non-uniformity is visually remarkable.

As described in the foregoing, according to the present invention, the occurrence of the color non-uniformity attributable to the order of shots of ink can be reduced even if the bi-directional printing is effected by application of different amounts of ink.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purpose of the improvements or the scope of the following claims.